

Colour Availability –

PVC-u Profiles & SureProtect Endure®

Standard colours

35 standard colours provide a colour choice to suit virtually any design scheme, from healthcare and education environments through to leisure and commercial office applications. Refer to the colour chart on the fourth page for details of specific product availability.

Textured Finish

Textured and through coloured to conceal the effects of impact and abrasion

Colour Matching

Important note: Due to the limitations of the printing process, colours within this catalogue should not be relied upon for colour matching. An accurate colour match can only be achieved by requesting the relevant product sample(s).

Light Reflectance Values

All Gradus wall protection colours have been measured for Light Reflectance and the Value (LRV) is detailed below each colour (values have been measured using the CIE Y value in accordance with BS 8493:2008+A1:2010). LRVs allow tonal contrast to be achieved between different surfaces to highlight features (e.g. handrails or door furniture), identify hazards or provide wayfinding. Colours selected should have an LRV that is 30 points different from the surrounding surface.

Improving access to buildings for all users in line with the Equality Act 2010 is fundamental to ensure that buildings are designed or refurbished to create an inclusive environment

NCS Colour References

Gradus is a member of NCS (Natural Colour System) and utilises the NCS reference codes shown above each colour. For further information visit www.ncscolour.com. Property of and used under licence from the Scandinavian Colour Institute AB, SCI-Sweden se, Stockholm 2004. See www.ncscolour.com for NCS-standard samples

Colour Contrast and Dementia Inclusive Environment

Colour and contrast can both be used to enable people with sight loss and dementia to identify different rooms and key features inside and outside of their homes. Good use of colour and contrast can facilitate independent living, for example, by supporting people to find their way around and to use fixtures and facilities unassisted.




The Dementia Services Development Centre at the University of Stirling have undertaken a review of the Gradus Wall Protection products and have rated its design in relation to dementia design principles and it's usability within a dementia-inclusive environment.


SureProtect Endure® is rated as Class 1a/b. Finishes within these ratings can be used throughout dementia applications. We recommend a minimum contrast of 30 points LRV for critical surfaces.

For further information on ratings go to www.gradus.com


Contrast



Blend



Natural

<p>Only available in SPE15</p>			
<p>038 Polar</p> <p>LRV: 80.14 NCS: 1002-B</p>	<p>001 Chalk</p> <p>LRV: 87.51 NCS: 0500-N</p>	<p>031 Alum</p> <p>LRV: 71.91 NCS: 1000-N</p>	<p>032 Flint</p> <p>LRV: 43.70 NCS: 3000-N</p>
<p>004 Granite</p> <p>LRV: 24.07 NCS: 5502-B</p>	<p>011 Pebble</p> <p>LRV: 59.08 NCS: 2005-R80B</p>	<p>002 Gravel</p> <p>LRV: 53.71 NCS: 2502-Y</p>	<p>035 Hessian</p> <p>LRV: 35.79 NCS: 4010-Y30R</p>
<p>003 Clay</p> <p>LRV: 33.86 NCS: 4000-N</p>	<p>014 Cinnamon</p> <p>LRV: 42.30 NCS: 3005-Y80R</p>	<p>009 Sienna</p> <p>LRV: 26.67 NCS: 4010-Y70R / 4005-Y70R</p>	<p>010 Bark</p> <p>LRV: 16.61 NCS: 6005-Y80R</p>
<p>005 Shale</p> <p>LRV: 17.88 NCS: 6500-N / 6502-Y</p>	<p>006 Ivory</p> <p>LRV: 81.98 NCS: 0505-Y30R</p>	<p>007 Wicker</p> <p>LRV: 70.36 NCS: 0510-Y30R</p>	<p>008 Sand</p> <p>LRV: 52.26 NCS: 2010-Y30R</p>
<p>013 Greige</p> <p>LRV: 38.97 NCS: 3005-Y20R</p>	<p>033 Slate</p> <p>LRV: 7.03 NCS: 8005-R80B</p>	<p>036 Black</p> <p>LRV: 5.08 NCS: 8502-B</p>	<p>Popular colours stocked in depth</p>

SPE20 sheet size 3,0m x 1,3m x 2,0mm Thickness. **Available in all colours**
 ▲ **SPE15** available in sheet size 2,44m x 1,22m x 1,5mm Thickness

Colour



021 Straw
LRV: 75.21
NCS: 0530-Y / 0530-Y10R



022 Apricot
LRV: 60.68
NCS: 0550-Y20R



027 Melon
LRV: 38.00
NCS: 1060-Y50R



028 Poppy
LRV: 16.31
NCS: 1080-R



034 Rose Quartz
LRV: 52.08
NCS: 1515-R20B



015 Lavender Grey
LRV: 37.18
NCS: 3010-R60B



030 Iris
LRV: 18.61
NCS: 4040-R50B



029 Garnet
LRV: 10.43
NCS: 4040-R20B



016 Glacier
LRV: 59.27
NCS: 1020-B



018 Azure
LRV: 45.14
NCS: 1040-R90B



017 Bluebell
LRV: 36.50
NCS: 2030-R70B



020 Denim
LRV: 16.91
NCS: 4040-R90B



024 Bamboo
LRV: 54.74
NCS: 1040-G50Y



023 Meadow
LRV: 54.63
NCS: 1030-G20Y



025 Emerald
LRV: 29.53
NCS: 3030-B80G / 3030-B70G



019 Ultramarine
LRV: 27.39
NCS: 3040-B20G

